

管状接头

特征

- 材质：316L
- 尺寸范围：1/4" 至 2"
- 抛光工艺：机械抛光或电解抛光
- 多种结构类型可以提供




尺寸说明

- 尺寸仅供参考，可能会有变动。如不能满足您的技术要求，请咨询anlok销售代表


型号和尺寸

同心变径接头




型号	接口类型和尺寸				尺寸 mm	
	端口1 Tube		端口2 Tube		L	LX
	外径 in.	壁厚 in.	外径 in.	壁厚 in.		
316L-U-6/4-TD/TD	3/8	0.035	1/4	0.035	69.9	34.8
316L-U-8/4-TD/TD	1/2	0.049	1/4	0.035	69.9	34.8
316L-U-8/6-TD/TD	1/2	0.049	3/8	0.035	69.9	34.8
316L-U-12/4-TD/TD	3/4	0.065	1/4	0.035	54.0	19.1
316L-U-12/6-TD/TD	3/4	0.065	3/8	0.035	54.0	19.1
316L-U-12/8-TD/TD	3/4	0.065	1/2	0.049	54.0	19.1
316L-U-16/4-TD/TD	1	0.065	1/4	0.035	60.0	25.4
316L-U-16/6-TD/TD	1	0.065	3/8	0.035	60.0	25.4
316L-U-16/8-TD/TD	1	0.065	1/2	0.049	60.0	25.4
316L-U-16/12-TD/TD	1	0.065	3/4	0.065	67.0	19.1
316L-U-24/4-TD/TD	1 1/2	0.065	1/4	0.035	73.0	38.1
316L-U-24/6-TD/TD	1 1/2	0.065	3/8	0.035	73.0	38.1
316L-U-24/8-TD/TD	1 1/2	0.065	1/2	0.049	73.0	38.1
316L-U-24/12-TD/TD	1 1/2	0.065	3/4	0.065	80.0	38.1
316L-U-24/16-TD/TD	1 1/2	0.065	1	0.065	80.0	38.1
316L-U-32/4-TD/TD	2	0.065	1/4	0.035	73.0	28.6
316L-U-32/6-TD/TD	2	0.065	3/8	0.035	73.0	38.1
316L-U-32/8-TD/TD	2	0.065	1/2	0.049	73.0	38.1
316L-U-32/12-TD/TD	2	0.065	3/4	0.065	80.0	38.1
316L-U-32/16-TD/TD	2	0.065	1	0.065	80.0	38.1
316L-U-32/24-TD/TD	2	0.065	1 1/2	0.065	90.0	38.1

90°弯通接头




型号	接口类型和尺寸		尺寸 mm	
	端口 Tube		L	R
	外径 in.	壁厚 in.		
316L-L-4-TD	1/4	0.035	50.0	14.2
316L-L-6-TD	3/8	0.035	52.0	23.0
316L-L-8-TD	1/2	0.049	54.0	19.1
316L-L-12-TD	3/4	0.065	66.0	28.4
316L-L-16-TD	1	0.065	69.0	38.1
316L-L-24-TD	1 1/2	0.065	95.3	57.2
316L-L-32-TD	2	0.065	123.0	76.2

45°弯通接头




型号	接口类型和尺寸		尺寸 mm	
	端口 Tube		L	R
	外径 in.	壁厚 in.		
316L-L1-4-TD	1/4	0.035	38.0	14.2
316L-L1-6-TD	3/8	0.035	39.0	23.8
316L-L1-8-TD	1/2	0.049	40.0	19.1
316L-L1-12-TD	3/4	0.065	49.0	28.4
316L-L1-16-TD	1	0.065	50.0	38.1
316L-L1-24-TD	1 1/2	0.065	70.0	57.2
316L-L1-32-TD	2	0.065	78.0	76.2

三通接头




型号	接口类型和尺寸		尺寸 mm	
	端口 Tube		L	LX
	外径 in.	壁厚 in.		
316L-T-4-TD	1/4	0.035	90.0	45.0
316L-T-6-TD	3/8	0.035	90.0	45.0
316L-T-8-TD	1/2	0.049	90.0	45.0
316L-T-12-TD	3/4	0.065	104.0	52.0
316L-T-16-TD	1	0.065	110.0	55.0
316L-T-24-TD	1 1/2	0.065	120.6	60.3
316L-T-32-TD	2	0.065	154.0	77.0

三通接头




型号	接口类型和尺寸				尺寸 mm		
	端口1, 2 Tube		端口3 Tube		L	Lx	Ly
	外径 in.	壁厚 in.	外径 in.	壁厚 in.			
316L-T-6/4-TD/TD	3/8	0.035	1/4	0.035	90.0	45.0	45.0
316L-T-8/4-TD/TD	1/2	0.049	1/4	0.035	90.0	45.0	45.0
316L-T-8/6-TD/TD	1/2	0.049	3/8	0.035	90.0	45.0	45.0
316L-T-12/4-TD/TD	3/4	0.065	1/4	0.035	94.0	44.0	47.0
316L-T-12/6-TD/TD	3/4	0.065	3/8	0.035	94.0	47.0	47.0
316L-T-12/8-TD/TD	3/4	0.065	1/2	0.049	94.0	44.0	47.0
316L-T-16/4-TD/TD	1	0.065	1/4	0.035	94.0	47.0	47.0
316L-T-16/6-TD/TD	1	0.065	3/8	0.035	94.0	47.0	47.0
316L-T-16/8-TD/TD	1	0.065	1/2	0.049	94.0	47.0	47.0
316L-T-16/12-TD/TD	1	0.065	3/4	0.065	110.0	55.0	55.0
316L-T-24/4-TD/TD	1 1/2	0.065	1/4	0.035	114.0	57.0	57.0
316L-T-24/6-TD/TD	1 1/2	0.065	3/8	0.035	114.0	57.0	57.0
316L-T-24/8-TD/TD	1 1/2	0.065	1/2	0.049	114.0	54.0	57.0
316L-T-24/12-TD/TD	1 1/2	0.065	3/4	0.065	136.0	62.0	68.0
316L-T-24/16-TD/TD	1 1/2	0.065	1	0.065	136.0	68.0	68.0
316L-T-32/4-TD/TD	2	0.065	1/4	0.035	114.0	57.0	57.0
316L-T-32/6-TD/TD	2	0.065	3/8	0.035	114.0	57.0	57.0
316L-T-32/8-TD/TD	2	0.065	1/2	0.049	114.0	57.0	57.0
316L-T-32/12-TD/TD	2	0.065	3/4	0.065	136.0	68.0	68.0
316L-T-32/16-TD/TD	2	0.065	1	0.065	136.0	68.0	68.0
316L-T-32/24-TD/TD	2	0.065	1 1/2	0.065	154.0	77.0	77.0

端帽



管外径 < 1/2 in.
示图



管外径 ≥ 1/2 in.
示图

型号	接口类型和尺寸		尺寸 mm
	端口 Tube		L
	外径 in.	壁厚 in.	
316L-TC-4-TD	1/4	0.035	12.7
316L-TC-6-TD	3/8	0.035	12.7
316L-TC-8-TD	1/2	0.049	12.7
316L-TC-12-TD	3/4	0.065	19.1
316L-TC-16-TD	1	0.065	25.4
316L-TC-24-TD	1 1/2	0.065	38.1
316L-TC-32-TD	2	0.065	38.1

选型说明

SS		-	U	-	4/4	-	TD/TD	-	EP
					端口1/端口2		端口1/端口2		
本体材质		接头形式		端口尺寸		端口形式		工艺	
SS	316不锈钢	U	直通接头	4	1/4 in.	TD	Tube管对焊 (管状接头)		机械抛光
316L	316L不锈钢	L	90°弯通接头	6	3/8 in.			EP	电解抛光
		L1	45°弯通接头	8	1/2 in.				
		T	三通接头	12	3/4 in.				
		TC	管帽	16	1 in.				
				24	1 1/2 in.				
				32	2 in.				

注1：选型代码为空的，为默认选项，在型号中不用体现

注2：选型说明只为产品选型提供参考，不能任意组合，标准型号请参考型号尺寸表，如不能满足您的技术要求，请咨询anlok销售代表